



Hands-on: Cray XC40 *Hornet* NPB-MZ-MPI / BT

VI-HPS Team

- Familiarise with usage of VI-HPS tools
 - complementary tools' capabilities & interoperability
- Prepare to apply tools productively to *your* applications(s)
- Exercise is based on a small portable benchmark code
 - unlikely to have significant optimisation opportunities
- Optional (recommended) exercise extensions
 - analyse performance of alternative configurations
 - investigate effectiveness of system-specific compiler/MPI optimisations and/or placement/binding/affinity capabilities
 - investigate scalability and analyse scalability limiters
 - compare performance on different HPC platforms
 - ...

- Set up preferred program environment compilers
 - PrgEnv-cray with CCE compilers is default
 - PrgEnv-gnu, PrgEnv-intel, PrgEnv-pgi also available

```
% module swap PrgEnv-cray PrgEnv-gnu
```

- Copy tutorial sources to your working directory, ideally on a parallel filesystem (\$SCRATCH)

```
% cd $SCRATCH
% tar zxvf ~hpcscabw/tutorial/NPB3.3-MZ-MPI.tar.gz
% cd NPB3.3-MZ-MPI
```

- The NAS Parallel Benchmark suite (MPI+OpenMP version)
 - Available from
<http://www.nas.nasa.gov/Software/NPB>
 - 3 benchmarks in Fortran77
 - Configurable for various sizes & classes
- Move into the NPB3.3-MZ-MPI root directory

```
% ls
bin/    common/   jobsript/   Makefile  README.install  SP-MZ/
BT-MZ/   config/   LU-MZ/     README    README.tutorial sys/
```

- Subdirectories contain source code for each benchmark
 - plus additional configuration and common code
- The provided distribution has already been configured for the tutorial, such that it's ready to "make" one or more of the benchmarks and install them into a (tool-specific) "bin" subdirectory

- Type “make” for instructions

```
% make
=====
=      NAS PARALLEL BENCHMARKS 3.3      =
=      MPI+OpenMP Multi-Zone Versions   =
=      F77                           =
=====

To make a NAS multi-zone benchmark type

      make <benchmark-name> CLASS=<class> NPROCS=<nprocs>

where <benchmark-name> is "bt-mz", "lu-mz", or "sp-mz"
      <class>          is "S", "W", "A" through "F"
      <nprocs>         is number of processes

[ ... ]

*****
* Custom build configuration is specified in config/make.def      *
* Suggested tutorial exercise configuration for HPC systems:    *
*   make bt-mz CLASS=C NPROCS=8                                     *
*****
```

- Specify the benchmark configuration
 - benchmark name: **bt-mz**, lu-mz, sp-mz
 - the number of MPI processes: **NPROCS=8**
 - the benchmark class (S, W, A, B, C, D, E): **CLASS=C**

```
% make bt-mz CLASS=C NPROCS=8
cd BT-MZ; make CLASS=C NPROCS=8 VERSION=
make: Entering directory 'BT-MZ'
cd ../sys; cc -o setparams setparams.c
../sys/setparams bt-mz 8 C
ftn -c -O3 -fopenmp bt.f
[...]
cd ../common; ftn -c -O3 -fopenmp timers.f
ftn -O3 -fopenmp -o ../bin/bt-mz_C.8 \
bt.o initialize.o exact_solution.o exact_rhs.o set_constants.o \
adi.o rhs.o zone_setup.o x_solve.o y_solve.o exch_qbc.o \
solve_subs.o z_solve.o add.o error.o verify.o mpi_setup.o \
../common/print_results.o ../common/timers.o
Built executable ../bin/bt-mz_C.8
make: Leaving directory 'BT-MZ'
```

Shortcut: % make suite

- What does it do?
 - Solves a discretized version of the unsteady, compressible Navier-Stokes equations in three spatial dimensions
 - Performs 200 time-steps on a regular 3-dimensional grid
- Implemented in 20 or so Fortran77 source modules
- Uses MPI & OpenMP in combination
 - 8 processes each with 6 threads should be reasonable for 2 compute nodes
 - bt-mz_C.8 should run in around 15-20 seconds
 - bt-mz_D.8 should take around 16x longer

- Copy jobscript and launch as a hybrid MPI+OpenMP application

```
% cd bin
% cp ../jobscript/hornet/run.pbs .
% less run.pbs
% qsub run.pbs
% cat run_<job_id>
NAS Parallel Benchmarks (NPB3.3-MZ-MPI) - BT-MZ MPI+OpenMP Benchmark
Number of zones:    8 x    8
Iterations:    200    dt:    0.000100
Number of active processes:    8
Total number of threads:        48 ( 6.0 threads/process)

Time step      1
Time step      20
[ ... ]
Time step    180
Time step    200
Verification Successful

BT-MZ Benchmark Completed.
Time in seconds = 16.02
```

Hint: save the benchmark output (or note the run time) to be able to refer to it later

- Edit config/make.def to adjust build configuration
 - Modify specification of compiler/linker: MPIF77
- Make clean and build new tool-specific executable

```
% make clean  
% make bt-mz CLASS=C NPROCS=8  
Built executable .../bin.$(TOOL)/bt-mz_C.8
```

- Change to the directory containing the new executable before running it with the desired tool configuration

```
% cd bin.$(TOOL)  
% cp ../jobsheet/hornet/$(TOOL).pbs .  
% qsub $(TOOL).pbs
```

```
#           SITE- AND/OR PLATFORM-SPECIFIC DEFINITIONS
#-----
# Items in this file may need to be changed for each platform.
#-----
# Configured for Cray XC with PrgEnv compiler-specific flags
#-----
#COMPFLAGS = -homp # cce
COMPFLAGS = -fopenmp # gnu
#COMPFLAGS = -openmp # intel
#COMPFLAGS = -mp # pgi
...
#-----
# The Fortran compiler used for MPI programs
#-----
MPIF77 = ftn
```

Default (no instrumentation)

```
# Alternative variant to perform instrumentation
#MPIF77 = scorep --user ftn

# PREP is a generic preposition macro
#MPIF77 = $(PREP) ftn
...
```

Hint: uncomment a compiler
wrapper to do instrumentation