



Hands-on: *INTI* Intel Haswell partition NPB-MZ-MPI / bt-mz_C.8

VI-HPS Team

Tutorial exercise objectives

- Familiarise with usage of VI-HPS tools
 - complementary tools' capabilities & interoperability
- Prepare to apply tools productively to *your* applications(s)
- Exercise is based on a small portable benchmark code
 - unlikely to have significant optimisation opportunities
- Optional (recommended) exercise extensions
 - analyse performance of alternative configurations
 - investigate effectiveness of system-specific compiler/MPI optimisations and/or placement/binding/affinity capabilities
 - investigate scalability and analyse scalability limiters
 - compare performance on different HPC platforms
 - ...

Compiler and MPI modules (INTI)

- Ensure that desired compiler and MPI modules (toolchain) are loaded first

```
% module list  
Currently Loaded Modulefiles:  
1) compil/x86_64 2) flavor/buildcompiler/intel/16 [...]  
16) mpi/openmpi/1.8.8
```

Alternatively switch compilers (gcc) and/or MPI (intelmpi) ...

- Set-up and load the required VI-HPS tools modules (when needed)

```
% module load datadir/formation cube/4.3.5 scorep/3.1 (scalasca/2.3.1 vampir/9.3.0)  
load module datadir/formation (Data Directory)  
load module cube/4.3.5 (Cube)  
load module scorep/3.1 (Score-P)
```

... but then you **must** specify the corresponding versions of tools!

- Copy tutorial sources to your \$SCRATCHDIR directory

```
% cd $SCRATCHDIR  
% tar zxvf $FORMATION_HOME/NPB3.3-MZ-MPI.tar.gz  
% cd NPB3.3-MZ-MPI
```

NPB-MZ-MPI Suite

- The NAS Parallel Benchmark suite (MPI+OpenMP version)
 - Available from:

<http://www.nas.nasa.gov/Software/NPB>

- 3 benchmarks in Fortran77
- Configurable for various sizes & classes
- Move into the NPB3.3-MZ-MPI root directory

```
% ls
bin/    common/   jobsctpt/  Makefile  README.install  SP-MZ/
BT-MZ/   config/   LU-MZ/    README     README.tutorial  sys/
```

- Subdirectories contain source code for each benchmark
 - plus additional configuration and common code
- The provided distribution has already been configured for the tutorial, such that it is ready to “make” one or more of the benchmarks
 - but config/make.def may first need to be adjusted to specify appropriate compiler flags

NPB-MZ-MPI / BT: config/make.def

```
#           SITE- AND/OR PLATFORM-SPECIFIC DEFINITIONS.  
#  
#-----  
# Configured for generic MPI with compiler-specific OpenMP flags  
#-----  
#COMPFLAGS = -fopenmp          # GNU/GCC compiler  
#COMPFLAGS = -openmp           # Intel14/15 compiler  
COMPFLAGS = -qopenmp         # Intel compiler  
...  
#-----  
# The Fortran compiler used for MPI programs  
#-----  
MPIF77 = mpif77  
  
# Alternative variant to perform instrumentation  
#MPIF77 = scorep --user mpif77  
  
# Use PREP is a generic preposition for instrumentation preparation  
#MPIF77 = $(PREP) mpif77  
...
```

Uncomment flags specification according to current compiler

Default (no instrumentation)

Hint: uncomment a compiler wrapper to do instrumentation

Building an NPB-MZ-MPI Benchmark

```
% make
=====
=      NAS PARALLEL BENCHMARKS 3.3      =
=      MPI+OpenMP Multi-Zone Versions   =
=      F77                           =
=====
```

To make a NAS multi-zone benchmark type

```
make <benchmark-name> CLASS=<class> NPROCS=<nprocs>
```

where <benchmark-name> is "bt-mz", "lu-mz", or "sp-mz"
<class> is "S", "W", "A" through "F"
<nprocs> is number of processes

[...]

```
*****
* Custom build configuration is specified in config/make.def  *
* Suggested tutorial exercise configuration for HPC systems:  *
*   make bt-mz CLASS=C NPROCS=8                                *
*****
```

- Type “make” for instructions

Building an NPB-MZ-MPI Benchmark

```
% make bt-mz CLASS=C NPROCS=8
make[1]: Entering directory `BT-MZ'
make[2]: Entering directory `sys'
cc -o setparams setparams.c -lm
make[2]: Leaving directory `sys'
../sys/setparams bt-mz 8 C
make[2]: Entering directory `../BT-MZ'
mpif77 -c -O3 -fopenmp          bt.f
                                [...]
mpif77 -c -O3 -fopenmp          mpi_setup.f
cd ..;/common; mpif77 -c -O3 -fopenmp      print_results.f
cd ..;/common; mpif77 -c -O3 -fopenmp      timers.f
mpif77 -O3 -fopenmp -o ..;/bin/bt-mz_C.8 bt.o
  initialize.o exact_solution.o exact_rhs.o set_constants.o adi.o
  rhs.o zone_setup.o x_solve.o y_solve.o exch_qbc.o solve_subs.o
  z_solve.o add.o error.o verify.o mpi_setup.o ..;/common/print_results.o
  ..;/common/timers.o
make[2]: Leaving directory `BT-MZ'
Built executable ..;/bin/bt-mz_C.8
make[1]: Leaving directory `BT-MZ'
```

- Specify the benchmark configuration
 - benchmark name: **bt-mz**, lu-mz, sp-mz
 - the number of MPI processes: **NPROCS=8**
 - the benchmark class (S, W, A, B, C, D, E): **CLASS=C**

Shortcut: % **make suite**

NPB-MZ-MPI / BT (Block Tridiagonal Solver)

- What does it do?
 - Solves a discretized version of the unsteady, compressible Navier-Stokes equations in three spatial dimensions
 - Performs 200 time-steps on a regular 3-dimensional grid
 - Implemented in 20 or so Fortran77 source modules
- Uses MPI & OpenMP in combination
 - 8 processes each with 8 threads should be reasonable for 2 compute nodes of INTI
 - bt-mz_B.8 should run in less than 4 seconds
 - bt-mz_C.8 should run in around 15 seconds

NPB-MZ-MPI / BT Reference Execution

```
% cd bin  
% cp ..../jobscript/inti/run.msub .  
% less run.msub  
% ccc_msub run.msub  
  
% cat npb_btmz_<job_id>.oe  
NAS Parallel Benchmarks (NPB3.3-MZ-MPI) - BT-MZ MPI+OpenMP Benchmark  
Number of zones: 8 x 8  
Iterations: 200 dt: 0.000300  
Number of active processes: 8  
Total number of threads: 48 ( 6.0 threads/process)  
  
Time step 1  
Time step 20  
[...]  
Time step 180  
Time step 200  
Verification Successful  
  
BT-MZ Benchmark Completed.  
Time in seconds = 18.78
```

- Copy jobscript and launch as a hybrid MPI+OpenMP application

Hint: save the benchmark output (or note the run time) to be able to refer to it later

Tutorial Exercise Steps

- Edit `config/make.def` to adjust build configuration
 - Modify specification of compiler/linker: `MPIF77`
- Make clean and then build new tool-specific executable

```
% make clean  
% make bt-mz CLASS=C NPROCS=8  
Built executable ..../bin.scorep/bt-mz_C.8
```

- Change to the directory containing the new executable before running it with the desired tool configuration

```
% cd bin.scorep  
% cp ..../jobsript/inti/scorep.msub .  
% ccc_msub scopr.p.msub
```