# Hands-on: *Archer* Cray XC30 NPB-MZ-MPI / bt-mz\_C.8

VI-HPS Team





























### **Tutorial exercise objectives**

- Familiarise with usage of VI-HPS tools
  - complementary tools' capabilities & interoperability
- Prepare to apply tools productively to your applications(s)
- Exercise is based on a small portable benchmark code
  - unlikely to have significant optimisation opportunities
- Optional (recommended) exercise extensions
  - analyse performance of alternative configurations
  - investigate effectiveness of system-specific compiler/MPI optimisations and/or placement/binding/affinity capabilities
  - investigate scalability and analyse scalability limiters
  - compare performance on different HPC platforms
  - **...**

# **Setup for exercises (Archer Cray XC30)**

Connect to your (ta002 training) account on Archer (with X11-forwarding enabled)

```
% ssh -X login.archer.ac.uk -1 <USER>
```

Select appropriate PrgEnv (cray, gnu, or intel: gnu recommended/assumed)

```
% module switch PrgEnv-cray PrgEnv-gnu
```

Copy tutorial sources to your WORK directory

```
% cd /work/ta002/ta002/$USER
% tar zxvf /work/ta002/shared/tutorial/NPB3.3-MZ-MPI.tar.gz
% cd NPB3.3-MZ-MPI
```



#### **NPB-MZ-MPI Suite**

- The NAS Parallel Benchmark suite (MPI+OpenMP version)
  - Available from:

### http://www.nas.nasa.gov/Software/NPB

- 3 benchmarks in Fortran77
- Configurable for various sizes & classes
- Move into the NPB3.3-MZ-MPI root directory

```
% ls
bin/ common/ jobscript/ Makefile README.install SP-MZ/
BT-MZ/ config/ LU-MZ/ README README.tutorial sys/
```

- Subdirectories contain source code for each benchmark
  - plus additional configuration and common code
- The provided distribution has already been configured for the tutorial, such that it is ready to "make" one or more of the benchmarks
  - but config/make.def may first need to be adjusted to specify appropriate PrgEnv compiler flags



# NPB-MZ-MPI / BT: config/make.def

```
SITE- AND/OR PLATFORM-SPECIFIC DEFINITIONS.
# Configured for Cray with PrgEnv compiler-specific OpenMP flags
#OPENMP = -homp # Cray/CCE compiler
OPENMP = -fopenmp # GNU/GCC compiler
#OPENMP = -qopenmp # Intel compiler
                                                                             Uncomment COMPILER flags
                                                                            according to current PrgEnv
# The Fortran compiler used for MPI programs
MPTF77 = ftn
                                                                                      Default (no instrumentation)
# Alternative variant to perform instrumentation
#MPIF77 = scorep --user ftn
                                                                                     Hint: uncomment a compiler
# PREP is a generic preposition macro for instrumentation preparation
\#MPIF77 = \$(PREP) ftn
                                                                                     wrapper to do instrumentation
```

34TH VI-HPS TUNING WORKSHOP (ONLINE, UK, 28-30 JULY 2020)



# **Building an NPB-MZ-MPI Benchmark**

```
% make
        NAS PARALLEL BENCHMARKS 3.3
        MPI+OpenMP Multi-Zone Versions
 To make a NAS multi-zone benchmark type
        make <benchmark-name> CLASS=<class> NPROCS=<nprocs>
 where <benchmark-name> is "bt-mz", "lu-mz", or "sp-mz"
                      is "S", "W", "A" through "F"
       <class>
       <nprocs>
                       is number of processes
  [...]
 * Custom build configuration is specified in config/make.def
 * Suggested tutorial exercise configuration for Archer:
        make bt-mz CLASS=C NPROCS=8
```

Type "make" for instructions

# **Building an NPB-MZ-MPI Benchmark**

```
% make bt-mz CLASS=C NPROCS=8
make[1]: Entering directory `BT-MZ'
make[2]: Entering directory `sys'
cc -o setparams setparams.c -lm
make[2]: Leaving directory `sys'
../sys/setparams bt-mz 8 C
make[2]: Entering directory `../BT-MZ'
ftn -c -O3 -fopenmp
                           bt.f
[...]
ftn -c -O3 -fopenmp mpi setup.f
cd ../common; ftn -c -O3 -fopenmp
                                    print results.f
cd ../common; ftn -c -O3 -fopenmp
                                          timers.f
ftn -03 -fopenmp -o ../bin/bt-mz C.8 bt.o
initialize.o exact solution.o exact rhs.o set constants.o adi.o
rhs.o zone setup.o x solve.o y solve.o exch qbc.o solve subs.o
 z_solve.o add.o error.o verify.o mpi setup.o ../common/print results.o
 ../common/timers.o
make[2]: Leaving directory `BT-MZ'
Built executable ../bin/bt-mz C.8
make[1]: Leaving directory `BT-MZ'
```

- Specify the benchmark configuration
  - benchmark name: bt-mz, lu-mz, sp-mz
  - the benchmark class (S, W, A, B, C, D, E): CLASS=**C**
  - the number of MPI processes: NPROCS=8

Shortcut: % make suite

# NPB-MZ-MPI / BT (Block Tridiagonal Solver)

- What does it do?
  - Solves a discretized version of the unsteady, compressible Navier-Stokes equations in three spatial dimensions
  - Performs 200 time-steps on a regular 3-dimensional grid
- Implemented in 20 or so Fortran77 source modules
- Uses MPI & OpenMP in combination
  - 8 processes each with 6 threads should be reasonable for 2 compute nodes of Archer
  - bt-mz\_C.8 should run in
    - around 20 seconds with PrgEnv-gnu
    - around 17 seconds with PrgEnv-cray
    - around 77 seconds with PrgEnv-intel

# **NPB-MZ-MPI / BT Reference Execution**

```
% cd bin
% cp ../jobscript/archer/run.pbs .
% less run.pbs
% qsub run.pbs
% cat mzmpibt.o<job id>
NAS Parallel Benchmarks (NPB3.3-MZ-MPI) - BT-MZ MPI+OpenMP Benchmark
Number of zones: 16 \times 16
Iterations: 200 dt: 0.000100
Number of active processes: 8
Total number of threads: 48 ( 6.0 threads/process)
Time step 1
Time step
            20
 [...]
Time step 180
Time step 200
Verification Successful
BT-MZ Benchmark Completed.
Time in seconds = 19.57
```

Copy jobscript and launch as a hybrid MPI+OpenMP application

Hint: save the benchmark output (or note the run time) to be able to refer to it later