

Analysing with ONE view

```
$ maqao oneview --create-report=one -options=..
```

ONE View general options:

- `-xp=exp_dir`: Path to directory storing the results. If omitted, directory `maqao_<timestamp>` will be created in the current directory.
- `--output-format=out_format`: Output format. Accepted values are `html` (default), `xlsx`, `text` and `all` (for all three formats).
- `--with-scalability=[on]|off(default)|weak`: Toggles scalability mode. The `scalability_params` array must be filled in the configuration file.

Using a configuration file for ONE View:

- `--config=cfg_path`: Uses file `cfg_path` to retrieve options. Options in `cfg_path` are similar to the execution options described below (without `--` and replacing `-` with `_`) and declared as Lua variables (`option="value"` or `option=number`). For instance: `run_command="<binary> -myoption"`
- `--create-config=sample_cfg`: Generates sample configuration file. If `sample_cfg` is omitted, `config.lua` will be created in the current directory.

Main execution options:

- `--binary=bin_path`: Path to application executable. Can be relative.
- `--run-command=run_cmd`: Command to run the application, using keyword `<binary>` to reference `bin_path`. If omitted, considered to be `./<binary>`

Parallel execution options:

- `--omp-num-threads=num`: Number of OpenMP threads. Overrides the `OMP_NUM_THREADS` environment variable.
- `--mpi-command=mpi_cmd`: MPI runtime invocation. Will prepend `run_cmd`.

Batch scheduling execution options:

- `--batch-script=script_path`: Path to job scheduler script. The script must have been modified to replace the application executable and its arguments with keyword `<run_command>`.
- `--batch-command=batch_cmd`: Command for invoking the job scheduler, using keyword `<batch_script>` to reference `script_path`.

Viewing reports:

- Text reports are displayed directly on the console output.
- HTML: open `<exp_dir>/RESULTS/<binary_name>_one_html/index.html` in a browser to display the HTML reports.
- XLSX reports are in file `<exp_dir>/RESULTS/<binary_name>_one_0_0.xlsx`
- The path to the reports is displayed at the end of ONE View analysis.

Sample invocations of ONE View

- Command line on interactive MPI run

```
$ maqao oneview --create-report=one --binary=my_path/my_app \
--mpi-command="mpirun -n 4" --omp-num-threads=2
```

- Command line for job scheduler script (script must be edited to replace `my_path/my_app -arg=foo` with `<run_command>`)

```
$ maqao oneview --create-report=one --binary=my_path/my_app \
--run-command="<binary> -arg=foo" \
--batch-script="my_script.job" \
--batch-command="my_jobsched <batch_script>"
```

- Using ONE View configuration file

```
$ maqao oneview --create-config=my_config.lua
{edit my_config.lua to fill all required variables}
$ maqao oneview --create-report=one --config=my_config.lua
```

- Compare existing ONE View reports

```
$ maqao oneview --compare-reports --inputs=exp_dir1,exp_dir2,... \
[-xp=output_dir]
```

Advanced: Invoking LProf / CQA separately

Profiling with MAQAO LProf

If *exp_dir* is omitted, a directory named *maqao_lprof_<timestamp>* will be created.

- Sequential / OpenMP profiling

```
$ maqao lprof [-xp=exp_dir] -- ./foo arg1 arg2 ...
```

- MPI / hybrid profiling

```
$ maqao lprof [-xp=exp_dir] --mpi-command="mpirun -n 32" \
-- ./foo arg
```

- Displaying profiling results

```
$ maqao lprof -xp=exp_dir -df # Functions profiling results
$ maqao lprof -xp=exp_dir -dl # Loops profiling results
```

Analysis with CQA

- Analysing a given loop or set of loops

id1, id2, id3 ... are the numerical loop identifiers returned by **LProf**.

```
$ maqao cqa ./my_app -loop=id1,id2,id3...
```

- Analysing all innermost loops in a given function or set of functions

```
$ maqao cqa ./my_app -fct-loops="regexp"
```

- Analysing the body of a given function or set of functions

```
$ maqao cqa ./my_app fct-body="regexp"
```

regexp is a regular expression: *foo* matches "foo1", "foo" or "afoo", while *^bar\$* matches "bar" only